

FIREWORLD AIR WATER FIRE EXTINGUISHER

Certified & Approved to AS/NZS 1841.2



Fire Extinguisher Features:

- Stainless Steel cylinder
- Filled and charged ready to use
- Powder coated with UV resistant paint finish
- Stainless steel handles and levers – suitable for aggressive environments.
- Heavy duty zinc plated brass valve with easy to read pressure indicator
- Wall hanging bracket
- Australian Standards Aluminium Inspection Tag supplied and fitted to extinguisher
- Schrader valve, 45 degrees from horizontal for easier recharging
- Fire extinguishers have been fire tested for the use in A Class fires. Rating is an indication of the level of fire testing achieved. All testing is carried out by fire professionals.
- All fire extinguishers should be serviced to the relevant, current Australian Standard. *AS1851 - Maintenance of Fire Protection Systems and Equipment*

FIREWORLD fire extinguisher is suitable for the following Applications:

- A Class Fires (paper, wood, textiles)
- The Air Water Extinguisher **should not be used** on B or E class fires



PRODUCT CODE	CAPACITY	FIRE RATING	AGENT	DISCHARGE TIME (approx)	DIMENSIONS (height x outside diameter in mm)	OVERALL MASS (approx)
FWAW	9.0Lt	4A	Water	80 sec	610mm x 193mm	12.5kg