



Exit Lights



Order Code	Model Code	Exit Light	Page
E1609	LWNE1609	Wide Body LED Exit Light	1
E1610	LWRE1610	Universal LED Exit Light	2
E1610B	LWRE1610-BLK	Universal LED Exit Light Black	3
E1611	LWRE1611	Slimline LED Exit Light	4
E1611B	LWRE1611-BLK	Slimline LED Exit Light Black	5
E1612	LWNE1612	Wall Mount LED Exit Light	6
E1703	LWJE1703	LED Recessed Exit Light	7
E1703B	LWJE1703-BLK	LED Recessed Exit Light Black	8
E1704	LWME1704	Twin Spot LED Emergency	9
E1711	LWNE1711	LED Weatherproof Exit Light	10
E1801	LWJBE1801	LED Jumbo Exit Light	11
E6030	LWUF6030	LED Ufofire	12
E6030B	LWUF6030-BLK	LED Ufofire Black	12
E6030S	LWUF6030-S	LED Surface Mount Ufofire	13
E6030SB	LWUF6030-S-BL	LED Surface Mount Ufofire Black	13
E013	LW013-E	LED Bulkhead Emergency	14
E013S	LW013-E-S	LED Bulkhead Emergency with Microwave Sensor	14
E210P	LWB210-PE	2ft LED Batten Diffused Emergency	15
E210W	LWB210-WE	2ft LED Batten Wireguard Emergency	15
E218P	LWB218-PE	4ft LED Batten Diffused Emergency	15
E218W	LWB218-WE	4ft LED Batten Wireguard Emergency	15
E210WP	LWWB210-E	2ft LED Weatherproof Batten Emergency	16
E218WP	LWWB218-E	4ft LED Weatherproof Batten Emergency	16
E1803	AL8B1803-E	LED Diffused Batten 20W TC Emergency	16
E1802	AL8B1802-E	LED Diffused Batten 20/40W TC Emergency	16
E1903WP	AL8B1903-E	LED Weatherproof Batten 20W TC Emergency	16
E1902WP	AL8B1902-E	LED Weatherproof Batten 20/40W TC Emergency	16
E4020	LWOO4020-E	20W LED Oyster Emergency	17
E4028	LWOO4028-E	28W LED Oyster Emergency	17
E34520	LWJU34520W-E	20W LED Oyster Emergency	17
E1905	LWRE1905	Universal LED Exit Light (Budget model)	18



CEILING MOUNT EXIT



ORDER CODE: E1609

MODEL NUMBER: LWNE1609

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall and Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
378mm	160mm	204mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D12.5 C90: D12.5	50/60	16 Hours	3 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Recessed	IP20	3.7

Spacing Table	Mounting Height (m)								
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0
D2.5 (m)	3.3	3.0	2.0	1.1					
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0			

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

Fireworld

UNIVERSAL EXIT



ORDER CODE: E1610

MODEL NUMBER: LWRE1610

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty

Dimensions

LENGTH	WIDTH	HEIGHT
350mm	73mm	208mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D12.5 C90: D8	50/60	16 Hours	3 Hours	40 C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Wall or Ceiling	IP20	3.7

Spacing Table	Mounting Height (m)								
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0
D2.5 (m)	3.3	3.0	2.0	1.1					
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0			

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



UNIVERSAL EXIT - BLACK



ORDER CODE: E1610B

MODEL NUMBER: LWRE1610-BLK

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
350mm	73mm	208mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D12.5 C90: D8	50/60	16 Hours	2 Hours	40C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Wall or Ceiling	IP20	3.7

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



BLADE UNIVERSAL EXIT



ORDER CODE: E1611

MODEL NUMBER: LWRE1611

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty

Dimensions

LENGTH	WIDTH	HEIGHT
350mm	73mm	220mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D8 C90: D4	50/60	16 Hours	2 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Wall or Ceiling	IP20	3.7

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

BLADE UNIVERSAL EXIT- BLACK



ORDER CODE: E1611B

MODEL NUMBER: LWRE1611-BLK

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 2 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
350mm	73mm	220mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D8 C90: D4	50/60	16 Hours	2 Hours	50oC	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Wall or Ceiling	IP20	4.8

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



WALL MOUNT EXIT



ORDER CODE: E1612

MODEL NUMBER: LWNE1612

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall and Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
378mm	160mm	74mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	CO: D10 C90: D8	50/60	16 Hours	3 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Recessed	IP20	3.7

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



RECESSED BLADE EXIT

ORDER CODE: E1703

MODEL NUMBER: LWJE1703



- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Recessed
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty

Dimensions

LENGTH	WIDTH	HEIGHT
430mm	100mm	195mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D6.3 C90: D4	50/60	16 Hours	2 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Recessed	IP20	3.7

Spacing Table	Mounting Height (m)								
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0
D2.5 (m)	3.3	3.0	2.0	1.1					
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0			

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



BLADE RECESSED EXIT - BLACK



ORDER CODE: E1703B

MODEL NUMBER: LWJE1703-BLK

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Recessed
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty

Dimensions

LENGTH	WIDTH	HEIGHT
430mm	100mm	195mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D6.3 C90: D4	50/60	16 Hours	2 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Recessed	IP20	3.7

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



EMERGENCY TWINSPOOT



FEATURES

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall Mount
- Easy testing and maintenance
- Non - Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty
- IP65
- Polycarbonate Body

INSTALLATION OPTIONS

- Wall Mounted

APPLICATIONS

- Garages
- Industrial
- Commercial

General Spec

Voltage	Cct	IP	Fitting Colour	Duration	Max.Temp	Battery Capacity
220-240v	6000k	65	White	3 Hours	40 C	2200mAh

Order Code.	Model No.	Description	Size	Classification
E1704	LWME1704	2 X 3W Emergency Twinspot IP65 Poly carbonate	273x68x290mm	C0=D2.5 C90=D40



WEATHERPROOF EXIT



ORDER CODE: E1711

MODEL NUMBER: LWNE1711

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall and Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty
- Weatherproof

Dimensions

LENGTH	WIDTH	HEIGHT
381mm	98mm	162mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D2.5 C90: D2	50/60	16 Hours	3 Hours	40°C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained	Recessed	IP65	3.7

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
 A.B.N 80 119 905 672
 Ph: 1300 733 064 Fx: (02) 85729930
 Unit 27 - 16 Bernera Road, Prestons. NSW 2170
 Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

Fireworld

JUMBO EXIT



ORDER CODE: E1801

MODEL NUMBER: LWJBE1801

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall Mount & Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
630mm	320mm	100mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D5	50/60	16 Hours	2 Hours	40C	2200mAh
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	40m	Maintained	Recessed	IP20	3.7

Spacing Table	Mounting Height (m)								
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0
D2.5 (m)	3.3	3.0	2.0	1.1					
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0			

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

EMERGENCY DOWNLIGHT



- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 2 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty
- 1.2 m flex and plug fitted (recessed only)

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	D40	50/60	16 Hours	2 Hours	50oC	2200mAh

Battery Type	Power Consumption	Cutout	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	85-135mm	Maintained	Ceiling	IP20	4.8

Spacing Table		Mounting Height (m)								
NATA Classification		2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0
D2.5 (m)		3.3	3.0	2.0	1.1					
D4.0 (m)		4.5	4.4	4.2	3.8	3.0	2.0			

Order Code	Model No	Mounting Option
E6030	LWUF6030	Recessed
E6030S	LWUF6030-S	Surface Mounted



EMERGENCY DOWNLIGHT - BLACK



- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained
- 2 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 years warranty
- 1.2 m flex and plug fitted (recessed only)

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	D40	50/60	16 Hours	2 Hours	50oC	2200mAh

Battery Type	Power Consumption	Cutout	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	85-135mm	Maintained	Ceiling	IP20	4.8

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Order Code	Model No	Mounting Option
E6030SB	LWUF6030-S-BLK	Surface Mounted
E6030B	LWUF6030	Recessed

Fireworld Australia Pty Ltd
 A.B.N 80 119 905 672
 Ph: 1300 733 064 Fx: (02) 85729930
 Unit 27 - 16 Bernera Road, Prestons. NSW 2170
 Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

EMERGENCY WEATHERPROOF BULKHEAD



FEATURES

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall & Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty
- Constant Current Driver
- Lithium Battery
- LED Panel

INSTALLATION OPTIONS

- Surface Mounted

APPLICATIONS

- Offices
- Garages
- Industrial
- Commercial
- Retail
- Hospitality
- Stairwells

General Spec

Voltage	Cct	IP	Fitting Colour	Duration	Max.Temp	Battery Capacity
220-240v	4000k	65	White	3 Hours	40 C	2200mAh

Order Code.	Model No.	Description	Diffuser	Body	Classification
E013	LW013-E	LED Bulkhead 24 w Emergency 4000k	OPAL	Die Cast	C0=D25 C90=D25
E013S	LW013-E-S	LED Bulkhead 24 w Emergency With Built in Microwave Sensor 4000k	OPAL	Die Cast	C0=D25 C90=D25

Fireworld Australia Pty Ltd
 A.B.N 80 119 905 672
 Ph: 1300 733 064 Fx: (02) 85729930
 Unit 27 - 16 Bernera Road, Prestons. NSW 2170
 Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au



EMERGENCY BATTENS



FEATURES

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall & Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty (including battery)
- Constant Current Driver
- Lithium Battery
- 2 x T8 Tubes

INSTALLATION OPTIONS

- Surface Mounted

APPLICATIONS

- Offices
- Garages
- Industrial
- Commercial
- Retail
- Hospitality

General Spec

Voltage	Cct	IP	Fitting Colour	Duration	Max.Temp	Battery Capacity
220-240v	6000k	20	White	3 Hours	40 C	2200mAh

Order Code.	Model No.	Description	Diffuser	Classification
E210P	LWB210-PE	2ft LED Batten 2 x 10w Emergency	Prismatic	C0=D5 C90=D20
E210WE	LWB210-WE	2ft LED Batten 2 x 10w Emergency	Wire Guard	C0=D5 C90=D20
E218P	LWB218-PE	4ft LED Batten 2 x 18w Emergency	Prismatic	C0=D5 C90=D20
E210WE	LWB218-WE	4ft LED Batten 2 x 18w Emergency	Wire Guard	C0=D5 C90=D20



EMERGENCY WEATHERPROOF BATTENS



FEATURES

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall & Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty
- Constant Current Driver
- Lithium Battery
- 2 x T8 Tubes
- IP65
- Tamper Proof Stainless Steel Clips

INSTALLATION OPTIONS

- Surface Mounted

APPLICATIONS

- Offices
- Garages
- Industrial
- Commercial
- Retail
- Hospitality

General Spec

Voltage	Cct	IP	Fitting Colour	Duration	Max.Temp	Battery Capacity
220-240v	6000k	65	White	3 Hours	40 C	2200mAh

Order Code.	Model No.	Description	Diffuser	Classification
E210WP	LWWB210-E	2ft LED Batten 2 x 10w Weatherproof Emergency	Clear	C0=D5 C90=D20
E218WP	LWWB218-E	4ft LED Batten 2 x 18w Weatherproof Emergency	Clear	C0=D5 C90=D20
E1903WP	AL8B1903-E	2ft LED Batten 2 x 10w Weatherproof Emergency	Opal	C0=D5 C90=D20
E1902WP	AL8B1902-E	4ft LED Batten 2 x 10w Weatherproof Emergency	Opal	C0=D5 C90=D20

Fireworld Australia Pty Ltd

A.B.N 80 119 905 672

Ph: 1300 733 064 Fx: (02) 85729930

Unit 27 - 16 Bernera Road, Prestons. NSW 2170

Po BOX 50 Casula Mall. NSW 2170.

www.fireworld.com.au



EMERGENCY OYSTER



FEATURES

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Wall & Ceiling Mount
- Easy testing and maintenance
- Maintained
- 3 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 3 year warranty
- Constant Current Driver
- Lithium Battery
- LED Panel

INSTALLATION OPTIONS

- Surface Mounted

APPLICATIONS

- Offices
- Garages
- Industrial
- Commercial
- Retail
- Hospitality
- Stairwells

General Spec

Voltage	Cct	IP	Fitting Colour	Duration	Max.Temp	Battery Capacity
220-240v	4000k	20	White	3 Hours	40 C	2200mAh

Order Code.	Model No.	Description	Diffuser	Size	Classification
E4020	LWOO4020-E	20 w LED Oyster Emergency 4000k	OPAL	350x105mm	C0=D25 C90=D25
E4028	LWOO4028-E	28W LED Oyster Emergency 4000k	OPAL	400x120mm	C0=D32 C90=D32

Fireworld Australia Pty Ltd
 A.B.N 80 119 905 672
 Ph: 1300 733 064 Fx: (02) 85729930
 Unit 27 - 16 Bernera Road, Prestons. NSW 2170
 Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au

UNIVERSAL EXIT - Vecta



ORDER CODE: E1905

MODEL NUMBER: LWRE1905

- Low power consumption
- 50,000hr LED - Energy efficient, long life
- Quick fit bracket for fast ceiling and wall mount
- Easy testing and maintenance
- Maintained and Non-Maintained (switchable)
- 2 hour runtime in emergency mode
- Designed and manufactured to AS/NZS2293.3
- 2 year warranty

Dimensions

LENGTH	WIDTH	HEIGHT
388mm	66mm	206mm

Specifications

Voltage	Classification	Frequency	Charging Time	Duration	Max.Temp	Battery Capacity
220-240	C0: D12.5 C90: D8	50/60	16 Hours	2 Hours	40 C	1500MaH
Battery Type	Power Consumption	Viewing Distance	Mode	Mounting Type	IP Rating	Battery Voltage (V)
Lithium	3 Watts	24m	Maintained and Non-Maintained	Wall or Ceiling	IP20	3.2

Spacing Table	Mounting Height (m)									
NATA Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	
D2.5 (m)	3.3	3.0	2.0	1.1						
D4.0 (m)	4.5	4.4	4.2	3.8	3.0	2.0				

Fireworld Australia Pty Ltd
A.B.N 80 119 905 672
Ph: 1300 733 064 Fx: (02) 85729930
Unit 27 - 16 Bernera Road, Prestons. NSW 2170
Po BOX 50 Casula Mall. NSW 2170.
www.fireworld.com.au